




PROXIMITY

CARD READERS ACCESS CONTROL



indoor use



outdoor use



post mount
with LED lighting




cards & tags
available as passive
or active

- Full line proximity card readers and cards
- Mullion, wall and post mount models
- Read ranges from 2-inches up to 5-feet (50.8mm to 152.4cm)
- Dual reading technology / active and passive
- 2 color LED (red/green), Piezo beeper
- 100% weatherproof
- 26-bit weigand format
- Reverse polarity protection

FEATURES


ACCESS CONTROL SOLUTIONS






CARD READERS


A unique feature of the DKS proximity card reader product line is that the card readers are compatible with both passive and active tags. This allows a mixing of different cards and tags to achieve desired read ranges in different locations without having to install a second card reader or carry two tags. These readers feature a cosmetically appealing design that will blend with any architectural design and offer high durability and reliability.




DKS Tiny




1815-230 & -231
(includes DKS 10)




DKS 10



DKS 20



DKS 30



DKS 70

Readers

Read Range

DKS Tiny / DKS 10 / DKS 20
 Up to 4" (101.6mm) with standard and ISO cards
 Up to 2" (50.8mm) with keytags
 Up to 12" (304.8mm) with IDA-150 active tags
 Up to 16" (406.4mm) with ID A-200 active tags
 DKS 30
 Up to 12" (304.8mm) with standard and ISO cards
 Up to 6" (152.4mm) with keytags
 Up to 3' (91.4cm) with IDA-150 active tags
 Up to 4' (121.9cm) with ID A-200 active tags
 DKS 70
 Up to 18" (457.2mm) with standard and ISO cards
 Up to 6" (152.4mm) with keytags
 Up to 3.5' (106.6cm) with IDA-150 active tags
 Up to 5' (152.4cm) with IDA-200 active tags

Dimensions

DKS Tiny: 1.77"W x 3.35"H x .6"D
 (44.9mm W x 85mm H x 15.2mm D)
 DKS 10: 1.82"W x 4.81"H x .87"D
 (46.2mm W x 122.1mm H x 22mm D)
 DKS 20: 3"W x 4.9"H x .87"D
 (76.2mm W x 124.4mm H x 22mm D)
 DKS 30: 4.8"W x 5.7"H x .8"D
 (121.9mm W x 144.7mm H x 20.3mm D)
 DKS 70: 12"W x 12"H x 1.2"D
 (304.8mm W x 304.8mm H x 30.4mm D)

Frequency

125 kHz

Output Format

26-bit wiegand

Operating Environment

-31°F to 149°F (-35°C to 65°C)

Safety Standards

FCC Part 15 / UL Listed

Warranty

5 year limited factory warranty

Input voltage / current

DKS Tiny/10/20: 5-12 VDC – 180mA
 DKS 30: 5-12 VDC – 200mA
 DKS 70: 12-24 VDC – 600 mA

LED / Beeper


DKS Tiny / 10 / 20 / 30 / 70
 2 color LED (Red, Green), Piezo Beeper

Optional

Surface / Gooseneck mount enclosure for the DKS 10 (part number 1815-230).
 Include Tracker Board with the mount enclosure (part number 1815-231).

Card & Tag Transmitters

Passive Tags



DKS 50


PROxmtr

DKS 80

DKS 170

DKS 50: Key Tags
 PROxmtr: Combination Prox Card and MicroPLUS or MicroCLICK RF Transmitters
 DKS 80: ISO Compliant Graphics Cards
 DKS 170: Standard Clamshell Cards
 DKS 150: Small Active Tag
 DKS 200: Large Active Tag

Active Tags



DKS 150

DKS 200