


ioProx™ Proximity Cards


ioProx Proximity cards ensure increased security with dual XSF and W26 encoded formats, while providing customers with the flexibility to choose from multiple card designs.



P10SHL
ioProx Standard Shell Card

Technical Specifications

| | |
|-----------------------|--------------------------------|
| Part Number | P10SHL |
| Typical read range | |
| P225/P225KP | up to 16.61 cm (6.54 in) |
| P325/P325KP | up to 20.83 cm (8.20 in) |
| P600 | up to 73 cm (29 in) |
| Card dimensions cm | 8.57 x 5.4 x 0.18 |
| Card dimensions in | 3.375 x 2.125 x 0.070 |
| Card construction | ABS and PVC |
| Color | White |
| Operating temperature | -45°C to 70°C (-50°F to 160°F) |
| Weight | 6.80 g (0.24 oz) |



P20DYE
ioProx Dye-sub Card

P30DMG
ioProx Dye-sub Card with
Blank Magnetic Stripe

Part Number P20DYE

Part Number P30DMG

Typical read range

| | |
|----------------------------|--|
| P225/P225KP | up to 8.50 cm (3.35 in) |
| P325/P325KP | up to 8.50 cm (3.35 in) |
| P600 | up to 48 cm (18.9 in) |
| Card dimensions cm | 8.57 x 5.4 x 0.079 |
| Card dimensions in | 3.375 x 2.125 x 0.031 |
| Card construction (P20DYE) | Thin, flexible polyvinyl chloride laminate |
| Card construction (P30DMG) | Multiple technology card, thin, flexible laminate with ABA standard three track Magnetic stripe not encoded |
| Color | Glossy white on both sides |
| Operating temperature | -45°C to 70°C (-50°F to 160°F) |
| Weight | 6.80 g (0.24 oz) |



P40KEY
ioProx Keytag

| | |
|-----------------------|--|
| Part Number | P40KEY |
| Typical read range | |
| P225/P225KP | up to 9.33 cm (3.67 in) |
| P325/P325KP | up to 10.37 cm (4.08 in) |
| P600 | up to 40 cm (15.7 in) |
| Keytag dimensions cm | 5.0 x 2.0 x 0.5 |
| Keytag dimensions in | 1.96 x 0.79 x 0.19 |
| Keytag construction | Ultrasonically welded, ABS shell and epoxy potted |
| Color | Grey |
| Operating temperature | -45°C to 70°C (-50°F to 160°F) |
| Weight | 5 g (0.18 oz) |



P50TAG

| | |
|-----------------------|--------------------------------|
| Part Number | P50TAG |
| Typical read range | |
| P225/P225KP | up to 8.41 cm (3.31 in) |
| P325/P325KP | up to 10.37 cm (4.08 in) |
| P600 | up to 27 cm (10.63 in) |
| Tag dimensions cm | 2.5 cm diameter |
| Tag dimensions in | 0.98 in diameter |
| Tag construction | PVC, self-adhesive back |
| Color | White |
| Operating temperature | -45°C to 70°C (-50°F to 160°F) |
| Weight | 1 g (0.04 oz) |